



OIL FREE PRODUCTS

2 – 30,000 HP / 15 – 725 PSI



OIL FREE SCROLL



SRL SERIES — SIMPLEX

Flow: 6 – 21 cfm
Pressure: 120 – 145 psig



SRL SERIES — MULTIPLEX

Flow: 30 – 129 cfm
Pressure: 122 – 145 psig

OIL FREE SCREW



DSP SERIES / 30 – 300 hp

Flow: 117 – 1303 cfm
Pressure: 125 psig



OFS SERIES / 100 – 350 hp

Flow: 446 – 1654 cfm
Pressure: 100 – 150 psig



DA13 / 100 – 200 hp

Flow: 427 – 785 cfm
Pressure: 100 – 150 psig



DW13 / 100 – 200 hp

Flow: 446 – 801 cfm
Pressure: 100 – 150 psig



DR13 / 100 – 200 hp

Flow: 428 – 785 cfm
Pressure: 125 psig




OFD1550 / 550 hp

Flow: 1550 cfm
Pressure: 125 psig

OIL FREE CENTRIFUGAL


T2 / 175 – 300 hp

Flow: 550 – 1645 cfm
Pressure: 60 – 130 psig




TX / 325 – 535 hp

Flow: 1050 – 2470 cfm
Pressure: 60 – 145 psig




TRA / 275 – 675 hp

Flow: 1175 – 2900 cfm
Pressure: 60 – 160 psig




TRE / 400 – 1500 hp

Flow: 1750 – 6450 cfm
Pressure: 20 – 230 psig




T3 / 525 – 1875 hp

Flow: 2075 – 8525 cfm
Pressure: 20 – 145 psig




TRX / 900 – 2300 hp

Flow: 5300 – 11,750 cfm
Pressure: 60 – 145 psig



f / 1340 – 30,000 hp

Flow: 1200 – 118,000 cfm
Pressure: 15 – 725 psig



For more information, contact OilFree@Sullair.com